
ATP PROJECTS
CONNECTION MATTERS

ZEROLINK
CONNECTION MADE SIMPLE

ZERO LINK · SOLDERLESS NEUTRIK CONNECTORS

speakON NL4 to Solderless Lever Terminals

NL4MP · 4-pole · Black
ATP part no. A-ATP-NL4MP-PW



01 DESCRIPTION

Neutrik speakON NL4MP 4-pole chassis connector in a black housing, fitted to an integrated PCB with Phoenix Contact lever terminals on the rear.

For pre-installed cables where wall plates, patch bays and panels are fitted on site. Strip, lift the lever, insert and close: no soldering needed.

02 FEATURES

- Vertical PCB mounting: 16 per 1U panel
- Tool-free, re-terminable lever terminals
- Strip guide printed on the PCB
- Neutrik Quick Lock, D-size flange
- Black only



03 SPECIFICATIONS

Dimensions (W × D × H)	26 × 51 × 48 mm
Wire range	0.2 – 4 mm²
Strip length	11 mm
Connector rated current	30 A rms continuous
Connector rated voltage	250 V AC
Terminal rating (LPTA 2,5)	24 A, 400 V
Contact resistance	≤ 3 mΩ
Mating cycles	> 5000
Operating temperature	–30 to +80 °C
Shell flammability	UL 94 HB


From Neutrik NL4MP and Phoenix Contact LPTA 2,5 data. The assembly is rated to its lowest-rated part.

04 WIRING

Terminal	Wire colour	Function	speakON pin
1	Red	Channel 1 +	1+
2	Blue	Channel 1 –	1–
3	Green	Channel 2 +	2+
4	Yellow	Channel 2 –	2–

Terminals numbered left to right, viewed from the rear. Colours follow the ATP standard for 4-core speaker cable.

Dimensions in mm · width 26



CE UKCA

Designed and manufactured in the UK
Designed and tested to meet the applicable UKCA and CE requirements.

ATP Projects Ltd · Unit 5 Bentley Industrial Centre, Farnham, Hampshire GU10 5NJ
VAT No. GB 164 139903 – Reg No. 8478777
Registered in England. Registered Office: Pine Cottages, Ash, GU12 6BZ

01483 338368
engineers@atpprojects.co.uk
www.atpprojects.co.uk